

EUROCUTTER®

d i f f e r e n t , b u t b e t t e r

LOADING



BFAP

BLOWER AND FAN AUTOMAT BFAP

Increase of productivity through networking of working processes

EUROCUTTER® Cutting Systems do not only make work easier, but also increase productivity.

Automatic lifting, lowering and automatic loading

Pile lifts and loading units reduce physical labour. The cutting material is lifted quickly and automatically to the optimal working height and then transferred to the High Speed Cutter or other peripheral equipment.

Operator bending is eliminated with an enormous increase of productivity.



Characteristic features SH...

Movable with rolls without load

Electro-hydraulic automatic lifting/lowering

Eliminating operator fatigue, ensuring continuous work at optimal working height

Aeration through air nozzles

mounted on sturdy and adjustable side frames

Blower

Air and duration adjustable

Closed hydraulic drive system

long life, almost wear resistant

Quick palette change

due to high speed lowering / lifting

Automatic safety cut-off

Control unit left or right hand side

Different types

for different palette sizes and weights



CE-Norm Safety Standard



Options

Ionizing air
Compressor

EUROCUTTER® BFAP		-3-600	-3-1000	-4-1000
Tragkraft	Kg	600	1000	1000
Maximum load.	lbs	1300	2200	3300
Palettengröße max.	mm	740 x 1070	740 x 1070	800 x 1230
Palett size max.	Inches	29 ½ x 42	29 ½ x 42	31 ½ x 48 ½
Max. Hubhöhe	mm	950	950	950
Max. Lift height	Inches	37 ¼	37 ¼	37 ¼
Luftverbrauch	L min	300	300	480
Air consumption	cft	10,6	10,6	17
Elektr. Leistung	KW	0,75	0,75	1,50
Electrical power	HP	1,00	1,00	1,25
Gewicht	Kg	690	800	880
Weight	lbs	1518	1764	1940
Spannung	Volt /	220 – 415	220 – 415	220 – 415
Voltage	Hz.	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz

Specifications are subject to change without notice



MZE Maschinenbau GmbH & Co. KG
Siemensstr. 21
D-65779 Kelkheim / Germany
Telefon +49 6195 994210
Fax +49 6195 994240
Email info@eurocutter.de
Internet <http://www.eurocutter.de>